

Claims

1. Apparatus for moving a stream of molten metal in a bath of the molten metal comprising:

a pumping member adapted to be disposed in a bath of a heated molten metal, and to move a stream of the molten metal as the pumping member is driven in a path of motion;

a housing at least partially enclosing the pumping member;

a shielding means carried on the pump housing, the shielding means having an internal shaft-receiving opening;

a power device adapted to be supported above the bath of molten metal, and to be actuated in a powered motion;

means for connecting the power device to the pumping member to move the pumping member in said path of motion, comprising;

a pumping shaft having an upper end connected to the power device so as to be moved when the power device is actuated, and a lower driving end connected to the pumping member to drive the pumping member in said path of motion when the power device is actuated;

the driving end of the shaft having a first coefficient thermal expansion and the socket having a different coefficient of thermal expansion; and

the shaft means being disposed in the shielded means out of contact with the molten metal, and forming a chamber between the shaft and the

21 shielding means sufficient to permit thermal expansion of the shaft without imposing a
22 radial thermal stress on the shielding means.

1 2. Apparatus as defined in claim 1, in which the pumping member is rotated
2 in said path of motion.

1 3. Apparatus as defined in claim 1, in which the power device is a motor
2 connected to the pumping shaft for rotating same.

1 4. Apparatus as defined in claim 1, in which the pumping member is an
2 impeller pumping element.

1 5. Apparatus as defined in claim 1, in which the pumping shaft is made of a
2 steel alloy with sufficient torque characteristics to rotate the pumping member in the
3 molten metal.

1 6. Apparatus as defined in claim 5, in which the pumping shaft is made of
2 stainless steel.

1 7. Apparatus as defined in claim 1, in which the shielding means comprises
2 an elongated tubular shield telescopically enclosing the pumping shaft, the tubular
3 shield having a lower end attached to the pump ^{member} housing, and an upper end, the tubular

4 shield having a length such that the upper end is disposed above the metal surface of
5 the bath of molten metal.

1 8. Apparatus as defined in claim 7, in which the pumping shaft is rotatably
2 connected to the pumping member, and the tubular shield encloses the pumping shaft
3 but does not rotate therewith.

1 ⁷
⁸ 9. Apparatus as defined in claim ⁶7, in which the pumping shaft is formed of a
2 steel alloy that has sufficient torque characteristics as to be capable of rotating the
3 pumping member in the molten metal, and
4 the tubular shield is formed of a ceramic material with sufficient
5 heat-resisting characteristics as to withstand the heat of the molten metal as the
6 pumping member is being rotated.

1 ⁸
¹⁰ 10. Apparatus as defined in claim ⁶7, in which the tubular shield includes:
2 an outer tubular shield having a lower end attached to the pump
3 ^{member} housing;
4 an inner tubular shield telescopically disposed in said outer tubular
5 shield and being attached thereto;
6 the inner tubular shield having a bore with a diameter greater than
7 the diameter of the pumping shaft, and enclosing the pumping shaft to form a chamber
8 therearound;

9 the lower end of the inner shield forming a shoulder; and
10 ^h ^h structure disposed on the lower end of the shaft engaging the
11 shoulder to locate the lower end of the shaft with respect to the inner shield.

Sub 2
1 11. Apparatus as defined in claim 7, in which the tubular shield means
2 includes:

3 an inner tubular shield telescopically disposed in said outer tubular
4 shield and being attached thereto;

5 the inner tubular shield having a bore with a diameter greater than
6 the diameter of the shaft, and enclosing the shaft so as to form a chamber therearound;

7 the lower end of the inner tubular shield being spaced from the
8 lower end of the outer tubular member to form a driving chamber;

9 a driving structure supported on the lower end of the shaft
10 enclosed within the outer shield; and

11 cement disposed in the outer shield having a socket
12 accommodating the configuration of said driving structure, the driving structure being
13 disposed in said socket but having a clearance therebetween to accommodate the
14 relative thermal expansion characteristics of said driving structure and the socket, but
15 permitting the driving structure to be rotated to engage the socket wall in the cement to
16 rotate the pumping member.

1 ²² ²¹ 12. Apparatus as defined in claim 11, in which the driving structure has a
2 tongue-shaped configuration.

1 ²³ 13. Apparatus as defined in claim ^{69 21} 11, in which the driving structure is
2 threadably attached to the lower end of the shaft.

1 ²⁴ 14. Apparatus as defined in claim ^{69 21} 11, in which the driving structure is
2 integrally attached to the lower end of the shaft.

1 ¹⁰ 15. Apparatus as defined in claim ⁹ 11, in which the clearance between the
2 driving structure and the socket is formed by the steps of:

3 forming the outer tubular shield with a lower blind end;
4 disposing a cement in the blind end of the outer tubular shield to
5 form a socket having the configuration similar to but larger than that of the driving
6 structure;
7 disposing a wax that turns to a gas when exposed to the heat in the
8 bath of molten metal, in said socket;
9 disposing the driving structure in the wax; and
10 telescopically inserting the inner tubular shield in the outer tubular
11 shield to engage the driving structure, and cementing the inner tubular shield to the
12 outer tubular shield to form a unitary tubular shield around the pumping shaft.

1 16. A combination, comprising:

2 pot means for containing a bath of molten metal;

Sub 13

3 a pumping member adapted to be disposed in a bath of a heated
4 molten metal, and to move a stream of molten metal as the pumping member is driven
5 in a path of motion;
6 a housing at least partially enclosing the pumping member;
7 a shielding means carried on the pump housing, the shielding
8 means having an internal shaft-receiving opening;
9 a power device adapted to be supported above the bath of molten
10 metal, and to be actuated in a powered motion;
11 means for connecting the power device to the pumping member to
12 move the pumping member in said path of motion, comprising;
13 a pumping shaft having an upper end connected to the power
14 device so as to be moved when the power device is actuated, and a lower driving end
15 connected to the pumping member to drive the pumping member in said path of motion
16 when the power device is actuated;
17 the driving end of the shaft having a first coefficient of thermal
18 expansion and the socket having a different coefficient of thermal expansion; and
19 the shaft means disposed in the shielding means out of contact
20 with the molten metal, and forming a chamber between the shaft and the shielding
21 means sufficient to permit thermal expansion of the shaft without imposing a radial
22 thermal stress on the shielding means.

1 17. A combination comprising:

2 pot means for containing a bath of molten metal;

3 a pumping member adapted to be disposed in a bath of a heated
4 molten metal, and to move a stream of the molten metal as the pumping member is
5 driven in a path of motion;

6 means on the pumping member forming a socket;

7 a power device adapted to be supported above the bath of molten
8 metal, and to be actuated in a power of motion;

9 means for connecting the power device to a pumping member to
10 move the pumping member in said path of motion, comprising;

11 the tubular shield enclosing the shaft.

1544
B3 18. Apparatus for moving a stream of molten metal in a bath of the molten
2 metal comprising:

3 a pumping member adapted to be disposed in a bath of a heated
4 molten metal, and to move a stream of the molten metal as the pumping member is
5 driven in a path of motion;

6 a power device adapted to be supported above the bath of molten
7 metal, and to be actuated in a powered motion;

8 means for connecting the power device to the pumping member to
9 move the pumping member in said path of motion, comprising;

10 a shaft adapted to be connected to the power device to be rotated
11 thereby;

^{tubular}
a shield means of a heat resistant material telescopically receiving

the shaft and having a length longer than the shield means so that the lower end of the

shield means extends beyond the lower end of the shaft;

means connecting the shaft to the shield means to rotate the shaft

^{the means}
and shield together; and

means connecting the shield means to the pumping member to

rotate the shield means and the pumping member together.

¹³
¹²
1 ¹⁹ Apparatus as defined in claim ¹⁸, in which the pumping member is rotated
2 in said path of motion.

¹⁴
1 ²⁰ Apparatus as defined in claim ¹⁸, in which the power device is a motor
2 connected to the shaft for rotating same.

¹⁵
1 ²¹ Apparatus as defined in claim ¹⁸, in which the pumping member is an
2 impeller pumping element.

¹⁶
1 ²² Apparatus as defined in claim ¹⁸, in which the shaft is made of a steel
2 alloy with sufficient torque characteristics to rotate the pumping member in the molten
3 metal.

¹⁷
1 ²³ Apparatus as defined in claim ¹⁸, in which the shaft is made of stainless
2 steel.

1 ¹⁰ 24. Apparatus as defined in claim ¹² 18, in which the shaft is formed of a steel
2 alloy that has sufficient torque characteristics as to be capable of rotating the member
3 in the molten metal, and
4 the shield means is formed of a ceramic material with sufficient
5 heat resisting characteristics as to withstand the heat of the molten metal as the
6 pumping member is being rotated.

1 ^{Sub A1} 25. Apparatus as defined in claim 18, including a pump housing at least
2 partially enclosing the pumping member, and in which the tubular shield means
3 includes an outer tubular shield having a lower end attached to the pump housing; and
4 an inner shield telescopically disposed in said outer tubular
5 element and being cemented thereto the shaft being connected to the inner shield.

1 26. Apparatus as defined in claim 18, including a pump housing at least
2 partially enclosing the pumping member, and in which the shield means includes:
3 an outer tubular shield having a lower end attached to the pump
4 housing,
5 an inner tubular shield telescopically disposed in said outer tubular
6 shield and being cemented thereto;

7 the inner tubular shield having a bore with a diameter greater than
8 the diameter of the pumping shaft, and enclosing the pumping shaft so as to form a
9 chamber therearound;

10 the lower end of the inner tubular member being spaced from the
11 lower end of the outer tubular member to form a shoulder;

12 a structure disposed adjacent the lower end of the drive shaft
13 having a diameter greater than the diameter of the bore of the inner tubular shield but
14 less than the diameter of the outer shield to form a shoulder, and the structure engages
15 the shoulder to locate the lower end of the shaft with respect to the tubular shield; and

16 cement disposed in the lower end of the outer shield with a socket
17 accommodating the configuration of the lower end of the shaft but having a clearance
18 therebetween to accommodate the relative thermal expansion characteristics of said
19 driving end to be rotated into the socket to rotate the pumping member.

20
21
22
23
24
25
26
27. Apparatus as defined in claim 26, in which the lower end of the shaft has
28 a tongue-shaped configuration.

29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
21

6 disposing wax that turns to gas when exposed to a heat in the bath
7 ^{Sub 44} of molten metal in said socket;
8 disposing the lower driving end of the shaft in the wax;
9 inserting the inner tubular member into the outer tubular member
10 so as to engage the driving end of the pumping shaft, and
11 cementing the inner tubular member to the outer tubular member to
12 form a unitary tubular shield around the shaft.

1 29. Apparatus as defined in claim 18, in which the shield means comprises an
2 inner tubular graphite shield telescopically receiving the shaft;
3 an outer tubular graphite shield telescopically receiving the shaft
4 and the inner tubular graphite shield; and
5 A ^{ceramic} ~~al~~ tubular shield telescopically receiving the shaft, the inner
6 graphite shield and the outer ~~graphite~~ shield.

1 30. Apparatus for moving a stream of molten metal in a bath of molten metal
2 having a metal level, comprising:
3 power means adapted to be supported above the metal level of the
4 bath;
5 a shaft having an upper end connected to the power means for
6 rotation thereby, and a lower end;

7 a pump housing adapted to be disposed in the bath of molten
8 metal;

9 the pump housing having a pumping chamber;

10 a pumping member disposed in the pumping chamber and
11 connected to the lower end of the pumping shaft for rotation therewith to produce a
12 stream of the molten metal;

13 the housing having a bottom inlet opening for receiving the molten
14 metal into the pumping chamber;

15 strainer means mounted on said inlet opening; and

16 the housing having feet for supporting the housing above the floor
17 of a pot containing a molten metal such that the bottom ^{inlet} opening faces toward the floor
18 of the pot when receiving molten metal therein through the inlet opening.

1 31. Apparatus for moving a stream of a molten metal in a bath of molten
2 metal, comprising:

3 power means adapted to be supported above the metal level of the
4 bath;

5 a shaft having an upper end connected to the power means for
6 rotation thereby, the shaft having a lower end;

7 a pump housing;

8 the pump housing having a pumping chamber, an inlet opening for
9 receiving molten metal into the pumping chamber;

the pumping member having a strainer plate having apertures for receiving molten metal into the pumping chamber as the pumping member is being rotated about an axis of rotation; and

a slinger rib mounted on the strainer plate adjacent the apertures and upstream thereof so as to strike debris carried into the stream toward the apertures, in a direction away from said inlet opening as the pumping member is being rotated.

33. Apparatus as defined in claim 32, in which the strainer plate has a convex configuration including a planar bottom bounded by a frusto-conical side wall, and the planar bottom has said apertures, and including other apertures in the frusto-conical side wall.

34. Apparatus as defined in claim 33, in which the slinger rib is mounted between the apertures in the ^{strainer} ~~slinger~~ bottom, and including another slinger rib mounted on the frusto-conical wall between the apertures therein.

35. Apparatus for moving a stream of molten metal in a bath of the molten metal beneath overhead structure, comprising:
a pump housing adapted to be disposed in a bath of molten metal below the metal level;

5 leg means disposed between the pump housing and the overhead
6 support structure, comprising:

7 a steel alloy leg having an upper end and a lower end, the
8 leg having a sufficient compressive strength to prevent the pump housing from rising in
9 the molten metal;

10 means for connecting the leg to the overhead support
11 structure;

12 a tubular shield means enclosing at least a portion of the
13 leg, and being formed of a material resistant to the heat of the molten metal; and

14 the tubular shield means having a lower end attached to the
15 pump housing, and an internal bore having a diameter greater than the diameter of the
16 leg to accommodate the leg's thermal expansion caused by the heat in the molten
17 metal bath.

1 36. Apparatus as defined in claim 35, in which the pump housing has an
2 opening, the tubular shield has a lower end disposed in said opening, and structure on
3 the lower end of the shield for preventing withdrawal of the shield through said opening.

1 37. Apparatus as defined in claim 36, in which said structure comprises a nut
2 threadably mounted on the lower end of the shield.

1 38. Apparatus as defined in claim 36, in which the structure is an integral
2 enlargement carried on the lower end of the shield, said enlargement being larger than
3 the opening in the housing.

1 39. Apparatus as defined in claim 36, in which the tubular shield is made of a
2 heat-resistant ceramic.

1 40. Apparatus as defined in claim 36, in which the shield means comprises an
2 outer ceramic tubular shield, and an inner ceramic tubular shield telescopically
3 received in the outer shield and cemented thereto, the inner shield being shorter than
4 the leg whereby both ends of the leg extend beyond the ends of the inner shield, and
5 upper fastener means are connected to the upper end of the leg and ^{engaged}engageable with
6 the upper end of the inner shield, and lower fastener means threadably fastened to the
7 lower end of the leg and engaged with the lower end of the inner shield for cooperating
8 with the fastener means in locating the leg in the bore of the inner shield.

1 41. Apparatus as defined in claim 40, in which the bore of the inner shield,
2 and the leg form a gas chamber, and including means for introducing an inert gas into
3 the gas chamber to form an oxygen-free environment around the leg.

1 42. Apparatus for moving a stream of a molten metal in a bath of the molten
2 metal, comprising:

overhead structure disposed above the molten metal level;
a pump having a housing, the housing having an upwardly facing
socket;
a vertical leg disposed between the overhead structure and the
pump housing;
the socket having a cylindrical side wall and an annular groove
therein;
the leg having an annular groove; and
a split retaining ring carried in the groove of the leg and in the
annular groove in the socket to prevent removal of the leg from the socket.

43. Apparatus as defined in claim 42, in which the split ring is diametrically
resilient so as to be squeezed toward the base of the groove in the leg to permit
passage of the ring into the socket opening.

44. Apparatus as defined in claim 42, in which a socket has a chamfered
opening to assist in squeezing the ring into the groove in the leg as the leg is being
passed into the socket.

052003 22506760

1 45. Apparatus for moving a stream of a molten metal in a bath of the molten
2 metal, comprising:
3 overhead structure disposed above the molten metal level;
4 a pump having a housing, the housing having an upwardly facing
5 socket;
6 a vertical leg disposed between the overhead structure and the
7 pump housing;
8 the socket having a cylindrical side wall and an annular groove
9 therein; and
10 including cement received in the groove in the socket for fastening
11 the leg to the housing.

ADD AS

add
B7